

GENERATOR SET

Power Ratings


Voltage, Frequency	PRP	ESP
400V, 50Hz $\cos\phi = 0.8$	205,8kVA / 164,6kW	225kVA / 180kW
Engine Make / Model :	FPT - N67TM7	
Generator Make / Model :	ALR - AA274H	
Control Panel :	ComAp AMF 9 Lite	
Charge Alternator [V / A] :	14 / 90	
Battery Charger [V / A] :	12 / 5	
Battery / Capacity [V / Ah] :	1 x (12V / 105Ah)	
Block Water Heater [W, V] :	1500 W, 230V	
ATS Model / Length x Width x Height * :	350A / 750x750x300	

Fuel Consumption

Load	110%	100%	75%	50%
[lt / h]	49	42,1	37,3	24

Fuel Tank Capacity [lt] : Open skid / Canopied : 215 / 270

Based on diesel fuel with a specific gravity of 0.85 and conforming to TS EN590 Class A2



Diesel Engine

Manufacturer :	FPT
Engine Model :	N67TM7
No. of Cylinders / Alignment :	6L
Bore / Stroke [mm] :	104 / 132
Compression Ratio :	17,5 : 1
Displacement [lt] :	6,7
Engine Speed [rpm] :	1500
Gross Engine Power ESP / PRP [kW] :	200 / 181,5

Generator

Manufacturer :	ALR
Alternator Model :	AA274H
Bearings Type :	Single
Insulation Class :	H
Winding Pitch :	2/3
No. of Wires Terminal :	6
Frequency / Poles :	50Hz / 4p
Voltage (Ph-Ph / Ph-N) :	400V / 230V
Output Power (163°C / 27°C) :	230kVA / 184kW

Prime Power (PRP)

A Prime rated generator set is capable of providing power to a varying load for an unlimited number of hours per year. Ten percent overload is allowed at one in 12 hours.

Emergency Standby Power (ESP)

A Standby rated generator set is capable of providing max. power to a varying load for 200 hours per year. No overload is allowed.

Standard Reference Conditions


A specified values are given for 25°C ambient temperature, 100m above sea level and 30% relative humidity.

Dimensions & Weights

	L x W x H (mm) / c x d (mm)	Wet (kg)
Canopy :	3100X1100X1930 / TBA	2150
	L x W x H (mm) / a x b x h (mm)	Wet (kg)
W/O Canopy :	2600X900X1670 / 900 x 700 x 510	1645

Dry = Without any liquid

Wet = With lube oil, coolant and fuel



Air Intake System :	Turbo Charged, After Cooled
Governor Type / Class 8528 :	Electronic
Total Oil Capacity [lt] :	17,2
Oil Type :	API CI-4, CH4/ 15W-40
Cooling System Capacity [lt] :	25,5
Recommended Fuel :	TS EN590, Class A2 Diesel
Emissions Compliance :	N/A
Housing - Flywheel :	SAE3/11,5

Regulation Type / Model :	AVR / SX440
Protection Class :	IP23
Efficiency (Pf 0,8 Prime)	93,3%
Voltage Regulation (Steady State) :	± 1.0%
THD (Total Harmonic Distortion) :	< 3.5%
	15% RFI kVA
Voltage Dip.	25% RFI kVA
	30% RFI kVA

f = 50Hz, $\cos\phi = 0$ is for given.