

GENERATOR SET

Power Ratings


Voltage, Frequency	PRP	ESP
400V, 50Hz cosφ = 0.8	439kVA / 351kW	486kVA / 388kW

Engine Make / Model :	FPT - C13TE6W
Generator Make / Model :	ALR - AA354C
Control Panel :	ComAp AMF 9 Lite
Charge Alternator [V / A] :	28 / 90
Battery Charger [V / A] :	24 / 5
Battery / Capacity [V / Ah] :	2 x 180 Ah
Block Water Heater [W] :	1500 W
ATS Model / Length x Width x Height * :	800A / 1000 x 850 x 320

Fuel Consumption

Load	110%	100%	75%	50%
[lt / h]	100,2	89,9	72,1	51,8
Fuel Tank Capacity [lt] : Open skid / Canopied :	550 / 650			

Based on diesel fuel with a specific gravity of 0.85 and conforming to TS EN590 Class A2



Diesel Engine

Manufacturer :	FPT
Engine Model :	C13TE6W
No. of Cylinders / Alignment :	6 / L
Bore / Stroke [mm] :	135 / 150
Compression Ratio :	16,5 : 1
Displacement [lt] :	12,88
Engine Speed [rpm] :	1500
Gross Engine Power ESP / PRP [kW] :	435 / 395

Generator

Manufacturer :	ALR
Alternator Model :	AA354C
Bearings Type :	Single
Insulation Class :	H
Winding Pitch :	2/3
No. of Wires Terminal :	6
Frequency / Poles :	50Hz / 4p
Voltage (Ph-Ph / Ph-N) :	400V / 230V
Output Power (163°C / 27°C) :	500kVA / 400kW

Prime Power (PRP)

A Prime rated generator set is capable of providing power to a varying load for an unlimited number of hours per year. Ten percent overload is allowed at one in 12 hours.

Emergency Standby Power (ESP)

A Standby rated generator set is capable of providing max. power to a varying load for 200 hours per year. No overload is allowed.

Standard Reference Conditions


A specified values are given for 25°C ambient temperature, 100m above sea level and 30% relative humidity.

Dimensions & Weights

	L x W x H (mm) / c x d (mm)	Wet (kg)
Canopy :	3350X1400X2780 / TBA	3800
	L x W x H (mm) / a x b x h (mm)	Wet (kg)
W/O Canopy :	3000X1300X1880 / 900 x 1000 x 700	2850

Dry = Without any liquid

Wet = With lube oil, coolant and fuel



Air Intake System :	Turbocharged & Aftercooled
Governor Type / Class 8528 :	Electronic / G2
Total Oil Capacity [lt] :	32
Oil Type :	API CI-4, CH4/ 15W-40
Cooling System Capacity [lt] :	38,1
Recommended Fuel :	TS EN590, Class A2 Diesel
Emissions Compliance :	N/A
Housing - Flywheel :	1-14

Regulation Type / Model :	AVR / SX440
Protection Class :	IP23
Efficiency :	93,8%
Voltage Regulation (Steady State) :	± 1.0%
THD (Total Harmonic Distortion) :	< 3.5%
	15% 300kVA
Voltage Dip.	25% 580kVA
	30% 725kVA

f = 50Hz, Voltage dip is given for Locked rotor at P.F.=0.6 .